

Avignon

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Pearlescent, protective topcoat

TEXTURE

Small grain

CHARACTERISTICS

Soft hand, small grain, subtle metallic

AVERAGE HIDE SIZE

50-55 sqft

THICKNESS

1.1-1.3mm

SUITABILITY

Residential, Hospitality, Contract, Marine

CONSIDERATIONS

Very durable & hard wearing

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 160cm x 170cm | 59in x 63in

vertical: 100cm x 210cm | 39in x 79in

PERFORMANCE

ABRASION

UNI EN ISO 11640

500 cycles dry: 4 Grey Scale

250 cycles wet: 5 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 7 & 8: Available on request

CAL 117(2013 Edition) : Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : > 20 N/mm

LIGHT FASTNESS

UNI EN ISO 105-B02 : >5 Blue Scale

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

FINISH ADHESION

UNI EN ISO 11644 : > 2 N/cm

