

Whistler

Cango

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Embossed, protective topcoat, tipped

TEXTURE

Embossed

CHARACTERISTICS

Ostrich-tipped

AVERAGE HIDE SIZE

50 sqft

THICKNESS

1.0-1.2mm

SUITABILITY

Residential, Hospitality, Contract, Marine

CONSIDERATIONS

Very durable, will have platelines

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

This is an embossed leather and so will have platelines from the embossing process. Each hide is effectively split into 4 panels – dimensions of each are approximately 80cm x 70cm | 31.5in x 27.6in.

PERFORMANCE

ABRASION

UNI EN ISO 11640

500 cycles dry: >3 Grey Scale

250 cycles wet: >3 Grey Scale

80 cycles perspiration: >3 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 7 & 8: Available on request

CAL 117(2013 Edition) | AB2998 compliant: Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : > 20 N/mm

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

LIGHT FASTNESS

UNI EN ISO 105-B02 : >5 Blue Scale

FINISHING ADHESION

UNI EN ISO 11644 : >2 N/cm

