Whistler

Croco

SPECIFICATIONS

CONTENT
European performance cowhide

FINISH
Embossed, protective topcoat

TEXTURE
Embossed

CHARACTERISTICS
Crocodile print

AVERAGE HIDE SIZE
50-55 sqft

THICKNESS
1.1-1.3mm

SUITABILITY
Residential, Hospitality, Contract, Marine

CONSIDERATIONS
Very durable, will have subtle platelines

ENVIRONMENTAL

REACH Compliant
Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

This is an embossed leather and so will have platelines. However, with this pattern it is very hard to see these lines. We often use the full hide vs only the panels shown here.

PERFORMANCE

ABRASION
UNI EN ISO 11640
500 cycles dry: >4 Grey Scale
250 cycles wet: >4 Grey Scale

FLAMMABILITY
BS 5852 Part 1/ Cigarette and Match: Pass
UNI EN ISO 1021-1 & 2: Pass
CRIB 5: Available on request
IMO FTP 2010 Part 7 & 8: Available on request
CAL 117(2013 Edition) : Pass
NFPA 260: Pass

FLEXING ENDURANCE
UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

LIGHT FASTNESS
UNI EN ISO 105-B02 : >4 Blue Scale

