Whistler

Evora

SPECIFICATIONS

CONTENT
European performance cowhide

FINISH
Aniline dyes, pigments, protective topcoat

TEXTURE
Smooth

CHARACTERISTICS
Shiny, firm hand

AVERAGE HIDE SIZE
50-55 sqft

THICKNESS
1.4-1.5mm

SUITABILITY
Residential, Hospitality, Contract, Marine

CONSIDERATIONS
Slight two-tone

PERFORMANCE

ABRASION
UNI EN ISO 11640
200 cycles dry: >3 Grey Scale
50 cycles wet: >3 Grey Scale

FLAMMABILITY
BS 5852 Part 1/ Cigarette and Match: Pass
UNI EN ISO 1021-1 & 2: Pass
CRIB 5: Available on request
IMO FTP 2010 Part 7 & 8: Available on request
CAL 117(2013 Edition) : Pass
NFPA 260: Pass

TEAR STRENGTH
UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS
UNI EN ISO 105-B02 : 4 Blue Scale

FLEXING ENDURANCE
UNI EN ISO 5402 : No finish damage cracks after 30,000 cycles

ENVIRONMENTAL

REACH Compliant
Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cmx 160cm | 59in x 63in
vertical: 100cm x 200cm | 39in x 79in

