

Laguna

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Aniline dyes, pigments, protective topcoat

TEXTURE

Distressed, flat

CHARACTERISTICS

Polished, distressed, aged look

AVERAGE HIDE SIZE

50-55 sqft

THICKNESS

1.0-1.1mm

SUITABILITY

Residential, Hospitality, Contract, Marine

CONSIDERATIONS

Durable finish, flame resistant, UV protected, inherent CRIB 5

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cm x 160cm | 47in x 51in

vertical: 100cm x 200cm | 35in x 63in

PERFORMANCE

ABRASION

UNI EN ISO 11640

500 cycles dry: >4 Grey Scale

150 cycles wet: >4 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Pass 

IMO FTP 2010 Part 7 & 8 : Pass 

CAL 117(2013 Edition) : Pass

NFPA 260: Pass

LIGHT FASTNESS

UNI EN ISO 105-B02 : >4/5 Blue Scale

TEAR STRENGTH

UNI EN ISO 3377-1 : >20N/mm

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

