Whistler

Livorno

SPECIFICATIONS

CONTENT
European performance cowhide

FINISH
Aniline dyes, pigments, protective topcoat

TEXTURE
Smooth

CHARACTERISTICS
Smooth, fine grain, soft hand

AVERAGE HIDE SIZE
45-50 sqft

THICKNESS
0.9-1.0mm

SUITABILITY
Residential, Hospitality, Contract, Marine

CONSIDERATIONS
Good for all applications

ENVIRONMENTAL

REACH Compliant
Meets European PFAS standards

PERFORMANCE

ABRASION
UNI EN ISO 11640
500 cycles dry: >4 Grey Scale
150 cycles wet: >4 Grey Scale
80 cycles perspiration: >4 Grey Scale

FLAMMABILITY
BS 5852 Part 1/ Cigarette and Match: Pass
UNI EN ISO 1021-1 & 2: Pass
CRIB 5: Available on request
IMO FTP 2010 Part 7 & 8: Available on request
CAL 117(2013 Edition) : Pass
NFPA 260: Pass

TEAR STRENGTH
UNI EN ISO 3377-1: >20 N/mm

LIGHT FASTNESS
UNI EN ISO 105-B02 : >5 Blue Scale

FLEXING ENDURANCE
UNI EN ISO 5402 : No finish damage cracks after 30,000 cycles

FINISH ADHESION
UNI EN ISO 11644 : >3.5 N/cm

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 130cm x150cm | 47in x 51in
vertical: 110cm x 170cm | 35in x 63in

