Whistler

Palm Springs

SPECIFICATIONS

CONTENT
European performance cowhide

FINISH
Aniline dyes, pigments, and resins, special finish for light resistance

TEXTURE
Medium, uniform grain

CHARACTERISTICS
Matte, soft hand

AVERAGE HIDE SIZE
50-55 sqft

THICKNESS
1.1-1.2mm

SUITABILITY
Residential, Hospitality, Contract, Marine, Outdoor

CONSIDERATIONS
Very durable and hard-wearing, meant for outdoor use when upholstered with suitable components. Engineered to withstand rain or shine.


ENVIRONMENTAL

REACH Compliant
Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cmx 160cm | 59in x 63in
vertical: 100cm x 200cm | 39in x 79in



PERFORMANCE

ABRASION
UNI EN ISO 11640
1000 cycles dry: >4 Grey Scale
350 cycles wet: >4 Grey Scale
500 cycles perspiration (ph8): >4 Grey Scale
800 cycles perspiration (ph5.5) >4 Grey Scale

FLAMMABILITY
BS 5852 Part 1/ Cigarette and Match: Pass
UNI EN ISO 1021-1 & 2: Pass
CRIB 5: Available on request
IMO FTP 2010 Part 8: Pass
CAL 117(2013 Edition) : Pass
NFPA 260: Pass

TEAR STRENGTH
UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS
UNI EN ISO 105-B02 : >7 Blue Scale (after 15 days xenon test)

FLEXING ENDURANCE
UNI EN ISO 5402 : No finish damage cracks after 100,000 cycles

COLOUR FASTNESS TO SEA WATER
After 8 hours storage: >4/5

FINISH ADHESION
UNI EN ISO 11644 : >2 N/cm