Whistler

Ray

SPECIFICATIONS

CONTENT
European performance cowhide

FINISH
Embossed, protective topcoat, tipped

TEXTURE
Embossed

CHARACTERISTICS
Stingray pattern

AVERAGE HIDE SIZE
50-55 sqft

THICKNESS
0.9-1.0mm

SUITABILITY
Residential, Hospitality, Contract, Marine

CONSIDERATIONS
Very durable, will have platelines, some colours show two-tone effect

ENVIRONMENTAL

REACH Compliant
Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

This is an embossed leather and so will have platelines from the embossing process. Each hide is effectively split into 4 panels – dimensions of each are approximately 80cm x 70cm | 31.5in x 27.6in.

PERFORMANCE

ABRASION
UNI EN ISO 11640
500 cycles dry: >4 Grey Scale
250 cycles wet: >4 Grey Scale

FLAMMABILITY
BS 5852 Part 1/ Cigarette and Match: Pass
UNI EN ISO 1021-1 & 2: Pass
CRIB 5: Available on request
IMO FTP 2010 Part 7 & 8: Available on request
CAL 117(2013 Edition) : Pass
NFPA 260: Pass

FINISH ADHESION
UNI EN ISO 11644 : > 2 N/cm

FLEXING ENDURANCE
UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

LIGHT FASTNESS
UNI EN ISO 105-B02 : >5 Blue Scale

