

Whistler

Evora

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Aniline dyes, pigments, protective topcoat

TEXTURE

Smooth

CHARACTERISTICS

Shiny, firm hand

AVERAGE HIDE SIZE

50 sqft

THICKNESS

1.4-1.5mm

SUITABILITY

Residential, Hospitality, Contract, Marine

CONSIDERATIONS

Slight two-tone

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cm x 160cm | 59in x 63in

vertical: 100cm x 200cm | 39in x 79in

PERFORMANCE

ABRASION

UNI EN ISO 11640

200 cycles dry: >3 Grey Scale

50 cycles wet: >3 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 7 & 8: Available on request

CAL 117(2013 Edition) | AB2998 compliant: Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS

UNI EN ISO 105-B02 : 4 Blue Scale

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 30,000 cycles

