

Whistler

Garda

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Technical Nubuck, buffed, pigments and waxes

TEXTURE

Nubuck

CHARACTERISTICS

Smooth and Soft

AVERAGE HIDE SIZE

50 sqft

THICKNESS

1.2-1.3mm

SUITABILITY

Residential, Hospitality, Contract, Marine, Outdoor

CONSIDERATIONS

Natural markings will be present, inherently water-resistant, stain resistance

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cm x 160cm | 59in x 63in

vertical: 100cm x 200cm | 39in x 79in

PERFORMANCE

ABRASION

UNI EN ISO 11640

250 cycles dry: >4/5 Grey Scale

150 cycles wet: >4 Grey Scale

100 cycles perspiration: >4 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 8: Pass 

CAL 117(2013 Edition) | AB2998 compliant: Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS

UNI EN ISO 105-B02 : >5 Blue Scale

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 50,000 cycles

COLOUR FASTNESS TO SEA WATER

after 8 hours storage: >4

FINISH ADHESION

UNI EN ISO 11644 : >5 N/cm

