

Whistler

Ontario

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Aniline dyes, pigments, protective topcoat

TEXTURE

Pebble grain

CHARACTERISTICS

Bright sheen, pebble grain, two-tone

AVERAGE HIDE SIZE

45 sqft

THICKNESS

1.4mm

SUITABILITY

Residential, Hospitality, Contract, Marine

CONSIDERATIONS

This is the only article like this in our collection

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 130cm x150cm | 47in x 51in

vertical: 110cm x 170cm | 35in x 63in

PERFORMANCE

ABRASION

UNI EN ISO 11640

500 cycles dry: >4 Grey Scale

100 cycles wet: >4 Grey Scale

50 cycles perspiration: >4 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 7 & 8: Available on request

CAL 117(2013 Edition) | AB2998 compliant: Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS

UNI EN ISO 105-B02 : >5 Blue Scale

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 30,000 cycles

FINISH ADHESION

UNI EN ISO 11644 : >2 N/cm

