

Whistler

Palm Springs

SPECIFICATIONS

CONTENT

European performance cowhide

FINISH

Aniline dyes, pigments, and resins, special finish for light resistance

TEXTURE

Medium, uniform grain

CHARACTERISTICS

Matte, soft hand

AVERAGE HIDE SIZE

50 sqft

THICKNESS

1.1-1.2mm

SUITABILITY

Residential, Hospitality, Contract, Marine, Outdoor

CONSIDERATIONS

Very durable and hard-wearing, meant for outdoor use when upholstered with suitable components. Engineered to withstand rain or shine.

ENVIRONMENTAL

REACH Compliant

Meets European PFAS standards

AVERAGE USABLE AREA

This is a natural product, the average usable area will vary depending on the size of the hide. Please use these dimensions as guidelines.

horizontal: 150cm x 160cm | 59in x 63in

vertical: 100cm x 200cm | 39in x 79in

PERFORMANCE

ABRASION

UNI EN ISO 11640

1000 cycles dry: >4 Grey Scale

350 cycles wet: >4 Grey Scale

500 cycles perspiration (ph8): >4 Grey Scale

800 cycles perspiration (ph5.5) >4 Grey Scale

FLAMMABILITY

BS 5852 Part 1/ Cigarette and Match: Pass

UNI EN ISO 1021-1 & 2: Pass

CRIB 5: Available on request

IMO FTP 2010 Part 8: Pass 

CAL 117(2013 Edition) | AB2998 compliant: Pass

NFPA 260: Pass

TEAR STRENGTH

UNI EN ISO 3377-1 : >20 N/mm

LIGHT FASTNESS

UNI EN ISO 105-B02 : >7 Blue Scale (after 15 days xenon test)

FLEXING ENDURANCE

UNI EN ISO 5402 : No finish damage cracks after 100,000 cycles

COLOUR FASTNESS TO SEA WATER

After 8 hours storage: >4/5

FINISH ADHESION

UNI EN ISO 11644 : >2 N/cm

